

TENAX RF 1



BI-ORIENTED NET

PHYSICAL AND DIMENSIONAL CHARACTERISTICS

Polymer	PP				
Mesh shape	QUADRANGULAR				
Color	GREY				
MD pitch	30 mm				
TD pitch	45 mm				
Unit weight	140 g/m ²				
Packaging	ROLLS WRAPPED WITH PE FILM			PIECES ON PALLET	
Roll width	1 m	1,5 m	2 m	Piece width	1 m
Roll length	50 m	50 m	50 m	Piece length	2 m
Covered area	50 m ²	75 m ²	100 m ²	Pieces for pallet	500,0
Roll diameter	0,23 m	0,23 m	0,23 m	Pallet size	0,8 x 1,1 x 2,1 m
Roll volume	0,06 m ³	0,08 m ³	0,11 m ³	Pallet volume	1,85 m ³
Roll weight	8,5 kg	12,8 kg	17 kg	Pallet weight	173 kg
Inner tubular diameter	76,8 mm				

MECHANICAL CHARACTERISTICS

Tensile strength MD	kN/m	9,3
Tensile strength TD	kN/m	17,0
Yield point elongation MD	%	16,0
Yield point elongation TD	%	13,0

The data contained in this publication are based on the knowledge available at the time of printing and may be subjected to amendments due to changes of the methods of testing and/or manufacturing. All dimensions and properties are reported as typical values.

TENAX nets are thermoplastic products subjected to shrinkage and deformations. MD: longitudinal direction. TD: transversal direction.

Tenax SpA Quality System has been assessed and registered in agreement with ISO 9001:2000 Standard.

TENAX®